

Wavelet Based Full Approximation Scheme for the Numerical Solution of Burgers' equation arising in Fluid Dynamics using Biorthogonal wavelet

S. C. Shiralashetti¹, L. M. Angadi² and A.B. Deshi³

¹ Department of Mathematics, Karnatak University Dharwad-580003, India

² Department of Mathematics, Govt. First Grade College, Chikodi – 591201, India

³ Department of Mathematics, KLECET, Chikodi – 591201, India

(Received April 26, 2019, accepted May 29, 2019)

Abstract: Wavelet based methods are the new development in the area of applied mathematics. Wavelets are mathematical tools that cut functions or operators into different frequency components, and then study each component with a resolution matching to its scale. In this paper, we proposed Biorthogonal wavelet based full-approximation scheme for the numerical solution of Burgers' equation arising in fluid dynamics using biorthogonal wavelet filter coefficients as prolongation and restriction operators. The proposed method gives higher accuracy in terms of better convergence with low computational time, which has been demonstrated through the illustrative problem.

Keywords: Biorthogonal wavelet; Multi-resolution analysis; Full approximation scheme; Burgers' equation; Fluid dynamics

1. Introduction

Partial differential equations (PDEs) arise frequently in Mathematical Physics and all branches of Engineering and other allied areas. For this reason the study of such equations is of great important. In this paper, we consider the solution of Burgers' equation, which is nonlinear Parabolic PDE. These equations are time dependent i.e. the solution depends not only on the spatial variable, but also the time dependent. The one dimensional Burgers' equation [1] is,

$$u_t + uu_x = \nu u_{xx}, \quad (1.1)$$

where ' ν ' is the coefficient of kinematic viscosity. This is the suitable model for considering problems associated with nonlinear convective terms, possesses the same form of convective linearity as the incompressible Navier–Stoke's equation and has readily evaluated to get exact solutions for many combinations of initial and boundary conditions.

In last two decades, many authors are applied various numerical methods to solve Burgers' equations, some of them are finite element method [2], Least-squares quadratic B-spline finite element method [3] etc. For large systems, these methods are inefficient in terms of both computer storage and computational cost.

In numerical analysis and computational science the development of effective iterative solvers for nonlinear systems of algebraic equations has been a significant research topic. Classical multigrid begins with a two-grid process. First, iterative relaxation is applied, whose effect is to smooth the error. In this paper, we describe how to apply multigrid to nonlinear problems. Applying multigrid method directly to the nonlinear problems by employing the method so-called Full Approximation Scheme (FAS). Nowadays it is recognized that FAS iterative solvers are highly efficient for nonlinear differential equations introduced by Brandt [4]. Full approximation scheme is suitable for nonlinear problems, which treats directly the nonlinear equations on finer and coarser grids. In FAS, a nonlinear iteration, such as the nonlinear Gauss-Seidel method is applied to smooth the error and the residual is passed from the fine grids to the coarser grids. Vectors from fine grids are transferred to coarser grids with Restriction operator (R), while vectors are transferred from coarse grids to the finer grids with a Prolongation operator (P) respectively. For a detailed treatment of FAS is given in Briggs et al. [5]. An introduction of FAS is found in Hackbusch et al. [6] and Wesseling [7]. Many authors applied the FAS for some class of differential equations. The full-approximation scheme (FAS) is largely applicable in increasing the efficiency of the iterative methods used to solve nonlinear system of algebraic equations. FAS are well-founded numerical method for solving nonlinear system of equations for approximating given differential equation. In this paper, we developed

the full-approximation scheme (FAS) for the numerical solution of Burgers' equation. However, when problems with discontinuous or highly oscillatory coefficients, multigrid procedure converge slowly with larger computational time or may break down. To overcome this difficulty, wavelet plays a very important role.

"Wavelets" have been very popular topic of conversations in many scientific and engineering gatherings these days. Some of the researchers have decided that, wavelets as a new basis for representing functions, as a technique for time-frequency analysis, and as a new mathematical subject. Of course, "wavelets" is a versatile tool with very rich mathematical content and great potential for applications. However wavelet analysis is a numerical concept which allows one to represent a function in terms of a set of basis functions, called wavelets, which are localized both in location and scale. The development of multiresolution analysis and the fast wavelet transforms by Avudainayagam and Vani [8] and Bujurke et al. [9-10] led to extensive research in wavelet multigrid schemes to solve certain differential equations arising in fluid dynamics. Shiralashetti et al. [11] had proposed Wavelet based multigrid method for the numerical solution of poisson equations.

This paper outspreads the same approach for the numerical solution of Burgers' equation arising in fluid dynamics i.e. Biorthogonal wavelet based full-approximation scheme (BWFAS) for the numerical solution of Burgers' equation. BWFAS is formulated rather than having one scaling and wavelet function, there are two scaling functions that may generate different multiresolution analysis, and accordingly two different wavelet functions.

The dual scaling and wavelet functions have the following properties:

- They are zero outside of a segment.
- The calculation algorithms are maintained, and thus very simple.
- The associated filters are symmetrical.
- The functions used in the calculations are easier to build numerically than those used in the Daubechies wavelets.

The organization of the paper is as follows. In section 2, Properties of Biorthogonal wavelets are given. Section 3 deals with Biorthogonal spline wavelet operators. Section 4 describes the method of solution. Numerical findings and error analysis are presented in section 5. Finally, conclusions of the proposed work are given in section 6.

2. Properties Biorthogonal Wavelets

The framework of the theory of orthonormal wavelets to the case of biorthogonal wavelets by a modification of the approximation space structure is extended by Cohen et al. [12]. In [13], Ruch and Fleet build a biorthogonal structure called dual multiresolution analysis that allows for the construction of symmetric scaling filters and that can incorporate spline functions. They used instead of scaling $\{a_n\}$ and wavelet $\{b_n\}$ filters, the new construct yields scaling $\{\tilde{a}_n\}$ and wavelet $\{\tilde{b}_n\}$ filters as decomposition and reconstruction. Instead of a single scaling function $\phi(x)$ and wavelet function $\psi(x)$, the dual multiresolution analysis requires a pair of scaling functions $\phi(x)$ and $\tilde{\phi}(x)$ related by a duality condition similarly, a pair of wavelet functions $\psi(x)$ and $\tilde{\psi}(x)$. To construct the BDWT matrix, the same thing is used in to build the orthogonal discrete wavelet transform matrix. Due to excellent properties of biorthogonality and minimum compact support, CDF wavelets can be useful and convenient, providing guaranty of convergence and accuracy of the approximation in a wide variety of situations.

Let's consider the (5, 3) biorthogonal spline wavelet filter pair,

$$\text{We have } \tilde{a} = (\tilde{a}_{-1}, \tilde{a}_0, \tilde{a}_1) = \left(\frac{1}{2\sqrt{2}}, \frac{1}{\sqrt{2}}, \frac{1}{2\sqrt{2}}\right)$$

$$\text{and } a = (a_{-2}, a_{-1}, a_0, a_1, a_2) = \left(\frac{-1}{4\sqrt{2}}, \frac{1}{2\sqrt{2}}, \frac{3}{2\sqrt{2}}, \frac{1}{2\sqrt{2}}, \frac{-1}{4\sqrt{2}}\right)$$

To form the highpass filters. We have $b_k = (-1)^k \tilde{a}_{1-k}$ and $\tilde{b}_k = (-1)^k a_{1-k}$.

The highpass filter pair b_k and \tilde{b}_k for the (5, 3) biorthogonal spline filter pair.

$$b_0 = \frac{1}{2\sqrt{2}}, b_1 = \frac{-1}{\sqrt{2}}, b_2 = \frac{1}{2\sqrt{2}} \text{ and } \tilde{b}_{-1} = \frac{1}{4\sqrt{2}}, \tilde{b}_0 = \frac{1}{2\sqrt{2}}, \tilde{b}_1 = \frac{-3}{2\sqrt{2}}, \tilde{b}_2 = \frac{1}{2\sqrt{2}}, \tilde{b}_3 = \frac{1}{4\sqrt{2}}$$

In this paper, we use the filter coefficients which are,